


XSF 364020
CH 1

Hexode

TELEFUNKEN

Kolbengrösse



Sockelschaltung

Heizspannung	U_f	13,0		Volt
Heizstrom	I_f	0,2		Amp.
Gitter-Anoden-Kapazität	C_{ag1}	< 0,003		pF
Anodenspannung	U_a	100—200	250	Volt
Schirmgitterspannung	U_{g3}	100	80	Volt
Schirmgitterspannung	U_{g4}	50	80	Volt
Gittervorspannung	$U_{g1} = U_{g3}$	— 2	— 20	— 2 — 20 Volt
Anodenstrom	I_a	4	< 0,015	3 < 0,015 mA
Steilheit	S_1	2	< 0,002	1,8 < 0,002 mAV
Innenwiderstand	R_i	1,5—2,0	> 10	2 > 10 MΩ
Schirmgitterstrom	I_{g2}	2	—	$I_{g2} + I_{g1}$ — mA
Schirmgitterstrom	I_{g1}	0,25	—	
				1,1 — mA

Für die Schaltung als Mischröhre betragen:

Gittervorspannung	U_{g3}	— 12	Volt
Oszillatorspannung	$U_{osz.}$	9	Volt eff.
Überlagerungssteilheit	S_c	0,55	mA/V
Dyn. Innenwiderstand	$R_{i \text{ dyn}}$	2	MΩ

Codewort: vbwqm

Gewicht max: 55 gr.



